

DK Film Hi-Tack Acrylic 3.5

Material Description: Double coated film tape with a modified high tack acrylic adhesive overall thickness of 3.5mils. Designed for demanding indoor and moderate outdoor applications. **Benefits**

Include: good initial tack, high performing long term adhesive bond, excellent UV resistance, and good plasticizer resistance.



Product Information	Description	
Carrier	0.5mil PET	
Adhesive	High Tack Acrylic	
Release Liner	Silicone Coated Paper	
Application Temperature (°F)	65 to 100	
Service Temperature (°F)	-20 to 275	
Adhesive and Carrier Thickness:	3.5 mils	

Adhesive	Typical Value	Test Method
Shear Resistance (minutes) 1in ² , 72°F 1000g Load:	4000	PSTC-107
90° Peel (lb/in):	10.5	PSTC-101
Quick Stick (lb/in):	2.0	PSTC-5

*Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.