

## THICK TWIN STICK® - 3/8" and 1/2"

**Material Description:** THICK TWIN STICK® is the double adhesive foam tape made especially for P-O-P displays and signage. It has a high tack adhesive for bonding to most surfaces including: corrugated, plastic, wood and metal. Available 1/32" to 2" thick the flexible foam carrier fills gaps that allow irregular surfaces to be joined. Thicker foams can be used to create a 3-D effect.



Product Information	Description
Carrier	Crosslinked Polyethylene
Adhesive	Rubber Based
Release Liner	Silicone coated paper
Application Temperature (°F)	65 to 100
Service Temperature (°F)	-20 to 150
Thickness (inch)	0.375 & 0.500

Foam	Typical Properties	Test Method
Color:	White / Black	Visual
Density (lb/ft³):	2	ASTM D3575
Tensile Strength (psi) MD:	69	ASTM D3575
Tensile Strength (psi) CD:	42	ASTM D3575
Elongation (% to break) MD:	136	ASTM D3575
Elongation (% to break) CD:	111	ASTM D3575
Compression Deflection @25% (psi):	5	ASTM D3575
Compression Set @50% compression:	31	ASTM D3575

Adhesive	Typical Value	Test Method
180° Peel Adhesion (lb/in)	8.0 min	PSTC-101
Shear Adhesion (hours): 1in², 10lb, 72°F	175	PSTC-107
Quick Stick (lb/in):	9.0 min	PSTC-5

\*Tests are performed on 2 mil PET

### Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.