



POLYOLEFIN

The ultimate robust barrier

A permanent rubber-based sensitive adhesive that is a flexible closed-cell foam used for dust, air and moisture sealing.



FEATURES:

- Dust, air and moisture sealing
- Good thermal barrier
- Conformability to irregular or textured surfaces
- General industrial
- Light seal
- Good for outdoor applications

APPLICATIONS:

- Air sealing
- Moisture sealing
- Glazing tape
- Shipping pads
- Packaging

SPECIFICATIONS:

- Test Method: ASTM D3575
- Density (lb/ft³): 2
- Compression Deflection: 2.5 to 5.9 psi
- Compression Set (50%): 41.2 max
- Service Temperature: -20° F to 150° F

Can't find your size?
We customize.

Try more
of our
weather stripping
+ gasketing
products!

STANDARD ROLLS

3" diameter core

Part Number	Thickness	Width	Length	Rolls/Carton
	in	in	ft	
472126	1/8	1/2	50	20
472127	1/8	3/4	50	13
472128	1/8	1	50	10
472139	3/16	1/2	50	20
472138	3/16	3/4	50	13
472140	3/16	1	50	10
472150	1/4	1/2	50	20
472152	1/4	1	50	10
472162	3/8	1/2	50	20
472174	1/2	1/2	25	20
472176	1/2	1	25	10

**Roll diameter listed is nominal with a tolerance of +/- 6%.*

NEED QUICK TURNAROUND?

Duraco manufactures and converts in-house, providing the convenient service of fast shipping and on-site tape experts. Contact us today.



LET'S TALK