



VINYL NITRILE NEOPRENE

Prominent elastic strength

A permanent rubber-based pressure sensitive adhesive that is oil and chemical resistant and a closed-cell foam.



FEATURES:

- Good oil and chemical resistance
- Non-stretch characteristics
- Highest flammability rating

APPLICATIONS:

- HVAC
- Roof Curb
- Doors
- Industrial Applications
- Dust Dealing
- Light Sealing

SPECIFICATIONS:

- Test Method: ASTM D1056
- Density (lb/ft³): 4 to 5.5
- Compression Deflection: 4 to 6 psi
- Compression Set (50%): 40 max
- Service Temperature: -20°F to 150°F
- Classification: 2C1, 2C2
- Flammability: FMVSS 302; UL94 HF-1 \geq 1/16"; UL94 V0 \geq 1/2"
- Flammability: FMVSS 302 UL94 HF-1 \geq 1/8"

Can't find your size?
We customize.

Try more
of our
weather stripping
+ gasketing
products!

STANDARD ROLLS

Part Number	Thickness	Width	Length	Rolls/Carton
	in	in	ft	
472116	1/8	1/2	50	20
472119	1/8	3/4	50	13
472118	1/8	1	50	10
472123	3/16	1/2	50	20
472121	3/16	3/4	50	13
472122	3/16	1	50	10
472124	1/4	1/2	50	20
472120	1/4	3/4	50	13
472117	1/4	1	50	10
472125	1/4	1-1/2	50	7

**Roll diameter listed is nominal with a tolerance of +/- 6%.*

NEED QUICK TURNAROUND?

Duraco manufactures and converts in-house, providing the convenient service of fast shipping and on-site tape experts. Contact us today.



LET'S TALK