

Product Specification Sheet



Duraco® ATG - 2.0 mils

Material Description: A 2.0 mil reverse wound adhesive transfer that consists of a glass stabilizer solvent-based permanent acrylic adhesive. The adhesive is coated on a brown kraft paper liner and wound on a 1" plastic core. This product is specifically designed to be used in Duraco ATG Dispensers. The ATG system automatically rewinds the tape's liner inside of the dispenser as the tape is applied (tape is dispensed without liner). Provides excellent adhesion to paper, most plastic films, and metal foils. Ultraviolet light has little or no effect on adhesive.



Product Information	Description
Carrier	None
Adhesive	Solvent Acrylic
Release Liner	SCK - Silicone Coated
Application Temperature (°F)	65 to 100
Service Temperature (°F)	-22 to 356
Adhesive Thickness:	2.0 mils
Adhesive	Typical Value
Peel Adhesion (oz/in)	55.0

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.

duraco.com

7400 Industrial Drive, Forest Park, IL 60130 | Phone: (866) 800-0775 | sales@duraco.com