

Duraco® Red

Material Description: Duraco Red is a clear PET film carrier double sided tape with red release liner. The acrylic adhesive combines good initial tack and a secure bond for hard to stick applications. It has strong plasticizer resistance, tolerates high temperature applications, and sticks well to UV coatings. Keeps graphics sharp and readable, too. Available in continuous rolls, spools, and cut pieces.



Product Information	Description	
Carrier	PET Film	
Adhesive	Acrylic	
Release Liner	MOPP Film	
Application Temperature (°F)	65 to 100	
Service Temperature (°F)	-14 to 300	
Thickness	8 mils	

Adhesive	Typical Value	Test Method
Shear Resistance:		
1in ² , 158°F (min) 500g Load:	10000 min	PSTC-107
1in ² , 72°F (min) 1000g Load:	10000 min	PSTC-107
90° Peel (lb/in):	4 min	PSTC-101
Probe Tack:		
(1 sec dwell - 454g Load)		
Force (g):	900 min	DI.3.5*
Area (g/s):	500 min	DI.3.5*

DI.3.5 is a Duraco internal test method.

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.