

Product Specification Sheet



1571

Material Description: 1571 is an unsupported adhesive tape with a water based acrylic adhesive, supplied with a red printed two sided silicone liner with overlaps at each edge to give a "finger-lift" for easy liner removal. Used for business forms, medical records, and envelopes.



Product Information		Description
Carrier		None
Adhesive		Acrylic
Release Liner		Silicone Coated Paper
Application Temperature (°F)		41 to 122
Service Temperature (°F)		-13 to 248
Adhesive Thickness:		1.0 mils

Adhesive	Typical Value	Test Method
Shear Resistance (minutes) 1in ² , 72°F 1kg Load:	10,000 min	PSTC-107
90° Peel (lb/in):	12.0	PSTC-101
Quick Stick (lb/in):	5.2	PSTC-5

*Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.

duraco.com

7400 Industrial Drive, Forest Park, IL 60130 | Phone: (866) 800-0775 | sales@duraco.com