

Remo Two® Clear - 1/32"

Material Description: REMO TWO® CLEAR is a removable acrylic foam tape made to remove cleanly even after extended periods of time from most hard non-delaminating substrates such as plastic, glass, finished wood or metal. Removable on both sides and features good absorptivity for impact and shock, medium solvent resistance and tackiness



| Product Information | | Description | |
|------------------------------|--|--------------------|--|
| Carrier | | Clear Acrylic Foam | |
| Adhesive | | Removable Acrylic | |
| Application Temperature (°F) | | 65 to 100 | |
| Service Temperature (°F) | | 40 to 175 | |
| Thickness (inch) | | 0.031 | |

| Adhesive | Substrate | Typical Value | Test Method |
|---------------------------|-------------|---------------|-------------|
| 90° Peel Adhesion (lb/in) | Powder Coat | 4.89 | PSTC-101 |
| | Aluminum | 3.69 | |
| | HDPE | 2.48 | |
| | Styrene | 4.08 | |
| | Glass | 4.35 | |

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.