

Duraco Transfer Tape Acrylic

Material Description: Duraco Transfer Tape Acrylic is an unsupported acrylic adhesive demonstrating good shear strength, high temperature resistance, good UV resistance, and good adhesion to flexible plastic.



| Product Information | Description |
|------------------------------|-----------------------|
| Carrier | None |
| Adhesive | Acrylic |
| Release Liner | Silicone Coated Paper |
| Application Temperature (°F) | 65 to 100 |
| Service Temperature (°F) | -20 to 275 |
| Adhesive Thickness: | 1.5 mils |

| Adhesive | Typical Value | Test Method |
|--|---------------|-------------|
| Shear Resistance (minutes) 1in ² , 72°F 10lb Load: | 150.0 | PSTC-107 |
| 90° Peel (lb/in): | 4.4 | PSTC-101 |
| Quick Stick (lb/in): | 1.9 | PSTC-5 |

*Tests are performed on 2 mil PET

Storage

Tape should be stored within its' original packaging, in a dry place at Room Temperature (72°F). If room temperature is not possible, the storage temperatures should not exceed 39°F to 100°F. When the tape is stored under these conditions, the shelf life would be 18 months from the date of shipment.

Duraco provides this information and recommendations for informative purposes only. The data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided.